

## Needlepoint Bi-Polar Ionization

Nu-Calgon introduces iWave, a new advanced air ionization technology to the HVACR market. This patented and OEM approved technology called needlepoint bi-polar ionization uses carbon fiber brushes to produce a refined electrical charge to proactively clean the air in residential and commercial buildings. The iWave approach produces equal amounts of positive and negative ions that reduce certain viruses and bacteria, particles, smoke, odors and VOCs in the air, creating a cleaner environment. iWave is UL 867 ozone standard certified to produce no unsafe levels of ozone.



## How Bi-Polar Ionization Works

iWave devices are bi-polar, meaning they use two emitters to create equal amounts of positive and negative ions. When these ions are injected into the air stream they reduce passing pollutants, gases and odors. When the ions are emitted into the airstream, they will reduce certain viruses and bacteria. Contact with ions has microbicidal effects on certain viruses and bacteria, which ultimately disrupt their surface proteins and render them inactive. The ions also attach to dust and other particles, causing them to band together until they are large enough to be caught by filters. iWave's technology generates the same ions that nature creates with lightning, waterfalls, ocean waves, etc. Nature uses ion energy to break apart molecules, naturally cleaning the air. iWave is UL 867 ozone standard certified to produce no unsafe levels of ozone.



## How iWave Ionization Differs from PCO Technology

Unlike iWave's bi-polar ionization method, Photo Catalytic Oxidation (PCO) technology uses UV light, commonly with titanium dioxide (TiO<sub>2</sub>) and often with other alloys, to create ionization. The Centers for Disease Control (CDC) has warned of cancerous risks involved with TiO<sub>2</sub>\* – not something you want in a building's air quality!

ASHRAE issued a position document in January 2015 on Filtration and Air Cleaning where they cautioned UV lamps used in many PCO devices can emit significant ozone – known to be harmful for human health. They also observed and reported on page 9 of the document "...potential of an incomplete oxidizing process, which produces by-products of reaction that can be more toxic or harmful than the original constituents (i.e. formaldehyde). The catalysts can be contaminated (poisoned) by airborne reagents and/or products of oxidation, which results in reduced or total efficiency failure of the process." Lastly, the PCO approach requires the replacement of the UV cell every year or two. Bi-polar ionization requires no replacement parts, and on the self-cleaning models, they are maintenance free for the life of the unit.

\*CDC Current Intelligence Bulletin 63





## Products:


### iWave®-R



4900-20

With technology installed in over 200,000 applications worldwide, iWave-R is a self-cleaning, bi-polar ionization system specially designed for residential duct air conditioning systems up to 6 tons (2400 CFM) in size. Needlepoint ionization actively treats air in the living space with no replacement parts, no maintenance for the life of the iWave and patented multi-voltage (24-240VAC). It can mount easily inside or outside of duct, or it can attach magnetically near indoor fan. iWave-R always works at peak performance, producing over 160 million ions/cc per polarity (320 million total ions/cc), more than any interior air quality product on the market. Patented self-cleaning design includes programmable cleaning cycle with alarm contact option. UL and cUL recognized. Three-year limited warranty.

### iWave®-M



4900-35

iWave-M is a flexible ion-generating bar that can treat IAQ in nearly any HVAC application. Its revolutionary circuit bar with special ion-generating needles suitable for any HVAC cooling coil up to 1,600 CFM. Plus, it can be shortened in the field to any size! Perfect for ducted package or ductless HVAC systems in living centers, hotels, commercial buildings, residential (including mini-splits), transport cooling coils or even in ice machines – applications where certain bacteria is an issue. Provides the highest level of ionization energy in the most compact size available on the market. UL and cUL recognized with patented universal voltage (110-240VAC). Virtually maintenance free with no replacement parts. Produces over 35 million ions/cc per foot per foot of flexible ribbon. Three-year limited warranty.

### iWave®-V



4900-40

With technology currently installed in over 200,000 applications worldwide, iWave-V is a versatile, low-maintenance bi-polar ionization generator for treating air in residential duct air conditioning systems up to 6 tons (2400 CFM) in size. Needlepoint ionization actively treats air in the living space with low maintenance and no replacement parts. Produces over 160 million ions/cc per polarity (320 million total ions/cc), more than any other interior air quality product on the market. Installs inside or outside of duct, or attaches magnetically near indoor fan. UL and cUL recognized. Three-year limited warranty.

### iWave®-C



4900-10

Although it can be used for residential applications, the original iWave-C is especially suitable for light commercial systems up to 12 tons (4800 CFM). iWave-C is a self-cleaning, bi-polar ionization generator for treating a building's air quality that does not require replacement parts in a year or two like competing technologies. iWave-C always works at peak performance, producing over 200 million ions/cc per polarity (400 million total ions/cc), making it superior to other market approaches. Special features include a programmable cleaning cycle, waterproof housing, digital display and integral alarm contact. Duct mount to air handler inside or outside of building. For systems larger than 12 tons, multiple iWave-C units can be applied. UL and cUL certified with patented multi-voltage input (24-240VAC). Three-year limited warranty.

<b>Application</b>	<b>iWave-R</b>	<b>iWave-V</b>	<b>iWave-C</b>	<b>iWave-M</b>
Residential - Mini-Split A/C Systems				X
Commercial - VRF A/C Systems				X
PTAC Systems				X
Residential Duct HVAC Systems	X	X	X	X
Light Commercial Duct HVAC Systems			X	X
Transport HVAC Systems				X
Industrial HVAC Systems				X
Ice Machines to Reduce Mold in Cabinet				X

<b>Features</b>	<b>iWave-R</b>	<b>iWave-V</b>	<b>iWave-C</b>	<b>iWave-M</b>
OEM Approved	X	X	X	X
Patented Self-Cleaning Technology	X		X	
No Replacement Parts	X	X	X	X
No Maintenance for life of iWave	X	*	X	*
Reduces Certain Bacteria and Viruses	X	X	X	X
Controls Odor (Cooking, Pet, VOCs)	X	X	X	X
Prevents/Eliminates Dirty Sock Syndrome	X	X	X	X
Controls Particles in Air	X	X	X	X
Reduces Smoke	X	X	X	X
Reduces Static Electricity	X	X	X	X
Multi-Voltage Input (24-240VAC)	X	24VAC	X	110-240VAC
Universal Mounting	X	X	Duct Mounted	X
Customizable Length				X
Digital Display/Weatherproof Housing			X	
Alarm Contact Option for Notification	X		X	
Replaceable Emitters	X		X	
Service Temperature Range	-40°F to 160°F	-40°F to 160°F	-40°F to 160°F	-40°F to 140°F
Limited Three Year Warranty	X	X	X	X

*\* The iWave-M, and iWave-V require low maintenance. The emitters may require a wipe with damp cloth from time to time to ensure ionizer tips are clear of particles. After power is turned off, the carbon bristles on the iWave-V should be looked at periodically (every time the air filter is replaced) to ensure they are clean for optimum performance.*

## Frequently Asked Questions:

### What makes iWave products unique?

- iWave products are patented ion-generating devices that produce the highest available ion outputs and are certified in accordance with UL867 to produce no unsafe levels of ozone. Not only that, there are self-cleaning options that require no maintenance (for the life of the unit), no replacement parts, universal voltage and universal mounting, making these highly versatile devices game-changers in the IAQ market. The devices offer a superior three-year warranty – other products require light/cell replacement in a year or two.

### How long will iWave products last?

- iWave products are designed to last for a very long time, up to the design life of the air conditioning equipment.

### What should be covered when installing an iWave-V or iWave-R in a residential A/C system?

- Install between the air filter and the indoor coil.
- The air current must flow through the “goal posts” (two emitters) so total ionization output is achieved.
- Attach IN or ON duct or indoor fan with air current flowing through “goal posts.” If installing on fan housing (shaft side), make sure self-tapping screws are used to secure device to housing, since the magnets alone may not be adequate if there is excessive vibration.
- Keep emitter brushes at least two inches from any metal surface. Electrical wires from the ionizer (or any wire in the equipment) must be kept away from emitter brushes.
- The products are only performing if there is air flow across the device.
- The devices pull low power (10VA), which allows maximum flexibility for installation.

### Any electrical hook-up guidelines for residential A/C systems?

- The iWave-C and iWave-R have multi-voltage capability between 24-240VAC for maximum versatility on electrical service options that are available for duct A/C systems. The iWave-M will handle between 110-240VAC voltage outputs typical for its intended application. The iWave-V requires 24 volts VAC.
- For residential duct A/C systems where 24/7 operation is desired, connect the device wires with “R” and “C” terminals/auxiliary board hook-ups, commonly available for 24VAC or 120VAC, but 240VAC is also an option.
- For the iWave-V running 24/7, the brushes may need to be cleaned a little more often, which is not an issue with the iWave-C/iWave-R because of the self-cleaning feature. Without air flow, the air is not being cleaned. With the device continuously on, the ions are quickly neutralized and there is no ion build-up in the home, smell at start-up or health concerns.
- Note: If the device is wired to be cycled with fan, for best results to quickly address IAQ in home, turn indoor fan to “On” position (continuously run) for 24-48 hours, then cycle with thermostat.
- For residential duct A/C systems where it is desirable to cycle the ionizer with the internal fan, connect the device wires with “R” and “G” terminals/auxiliary board hook-ups. Another easy option is to add a 24VAC or 120VAC current relay to the wire of the blower so it energizes the ionizer every time the blower is energized.
- Note: Depending on circumstances and what is being powered by a commonly used 40VA transformer, another 40VA foot-mounted transformer may be needed to power the ionizer.

